

## VISTA-15P

### VISTA® CONTROL PANEL



Honeywell's versatile VISTA-15P is the ideal choice for any residential installation. VISTA-15P gives you the ability to send alarm signals and upload/download via an Internet Protocol (IP), improving the speed at which information can be delivered to and from the control panel. In addition, when used with an AlarmNet® Internet or 4G communicator, the

VISTA-15P can be installed in premises without TELCO lines. Hardwired expansion, graphic keypad support, two-wire smoke detectors, scheduling options and a host of end-user and installer features separate the VISTA-15P from all other six-zone panels – offering you and your customers the most panel for the dollar.

## FEATURES

- IP alarm reporting and uploading/downloading capability for Internet and Intranet use via iGSMV4G, 7845i-ENT, GSMV4G or GSMX4G
- Six on-board hardwired zones
  - 16 hardwired expansion zones totalling 22
  - 26 wireless expansion zones
- Supports two graphic touchscreen keypads
- Eight independent keyfob zones allow wireless keys to be programmed without using any of the 26 zones
- Eight output devices
  - Relays (Model 4204 Relay Modules, or 4229 Expansion Module)
- Two low current on-board trigger outputs
- 50 Event Log viewable at system keypads with time/date stamp
- 32 system user codes
- Two installer configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes

- Multiple actions on output devices depending on system "state"
  - Turns light off when system arms
  - Turns same lights on when system disarms
  - Flashes same lights when system is in alarm
- Built-in phone line cut monitor with programmable delay and annunciation options
  - Display on system keypads
  - Trigger local sounders
  - Trigger system bell
- Supports four-wire and up to 16 two-wire smokes
  - Works with Sentrol CleanMe™ maintenance signal

### Security Dealer Features

- Automatic System Load Shed
  - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries.
- Dynamic Signaling
  - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet Radio

### Valuable End-user Features

- Now viewable on system keypads:
  - Exit countdown
  - Time and date display\*
  - Event log\*
- Auto keypad backlighting on entry
- Keyswitch arming
- Programmable macro buttons and single-button arming
- A variety of wireless remote controls for single-button operation
- User Scheduling
  - Latchkey reports to pagers
  - Auto arm/disarm
  - "User access" time windows
- Supports up to two numeric pagers
- VIP Module allows system control from any touchtone phone
- Chime by zone
- Fully compatible with Honeywell Total Connect™ Remote Services

\*Requires custom alpha keypad

# VISTA-15P

## VISTA® CONTROL PANEL

### SPECIFICATIONS

#### Electrical

- Aux. power 12VDC, 600mA maximum
- Seven hour standby at 400mA aux. load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0 amps max.
- For UL installations, combined aux. and alarm output cannot exceed 700mA

#### Output Control

- Supports a maximum of eight output devices (combination of relays and/or X-10) plus two onboard triggers

#### Zones

- Six hardwired zones
- Selectable response 10msec, 350msec, 750msec
- 16 selectable zone types plus two configurable zone types
- Programmable swinger suppression

#### Expansion Devices

- 4219 – Eight hardwired zones – 16mA
- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)
- 4229 – Eight hardwired zones and two relays – 36mA (each active relay draws an additional 40mA)

#### Accessories

- iGSMV4G Internet and Digital Cellular Communicator with Remote Service Capability
- 7845i-ENT Enterprise Internet Communicator
- GSMV4G Digital Cellular Communicator with Remote Service Capability

- GSMX4G Digital Cellular Communicator for VISTA Control Panels
- 5881ENL supports up to 8 zones – 60mA
- 5881ENM supports up to 16 zones – 60mA
- 5881ENH supports up to 48 zones – 60mA
- 5883 Transceiver supports up to 26 zones – 80mA

#### Keypads

- 6162 Custom Alpha Security Keypad – 40mA/120mA
- 6162V Voice Custom Alpha Security Keypad – 60mA/190mA
- 6162RF Custom Alpha Receiver/Security Keypad – 120mA/210mA
- 6152 Fixed-English Security Keypad – 40mA/70mA
- 6152V Voice Fixed-English Security Keypad – 60mA/190mA
- 6152RF/6152RFFR Fixed-English/French Receiver/Security Keypad – 80mA/105mA
- 6152ZN/6152ZNFR Fixed-English/French Security Keypad with Hardwired Zone – 35mA/80mA
- 6148 Fixed English LCD – 30mA/55mA
- 6280 Color Graphic Touchscreen Keypad with Voice
- Tuxedo Touch™ (TUXW) Color Graphic Voice Touchscreen Security Keypad and Home/Business Controller (White)
- Tuxedo Touch with Integrated Wi-Fi® (TUXWIFIW) Color Graphic Voice Touchscreen Security Keypad and Home/Business Controller with Integrated Wi-Fi (White)

#### Agency Listings

##### ETL listing

- Residential Fire and Burglary:
  - Household Fire Warning System Units – ANSI/UL 985, 2000/05/26 (5th edition) with revisions up to 2004/04/29

##### Smoke Detectors

- Supports up to 16 two-wire smoke detectors
- Supports four-wire smoke detectors

##### Communications

- iGSMV4G Internet and Digital Cellular Communicator with Remote Service Capability
- 7845i-ENT Enterprise Internet Communicator
- GSMV4G Digital Cellular Communicator with Remote Service Capability
- GSMX4G Digital Cellular Communicator for VISTA Control Panels
- Touchtone or pulse
- Formats supported
  - ADEMCO® Contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
  - Split
  - Dual
  - Split/Dual – True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

### ORDERING

<b>VISTA-15P</b>	Control Panel
<b>VISTA-15PSIA</b>	Control Panel for CP-01 SIA certifications

#### For more information:

[www.honeywell.com/security](http://www.honeywell.com/security)

#### Automation and Control Solutions

Honeywell Security Products Americas  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747  
1.800.467.5875  
[www.honeywell.com](http://www.honeywell.com)

L/VISTA15PD/D  
December 2013  
© 2013 Honeywell International Inc.

# Honeywell