

# AL624ET

## Linear Power Supply/Charger Kit

### Description

Altronix AL624ET power supply/charger kit converts a 115VAC 60Hz input into 12VDC output. This general purpose power supply has a wide range of applications for access control, security, and CCTV system accessories that require additional power.



AL624ET

### Specifications

#### Input

Voltage 115VAC, 60 Hz, 1.2A.

#### Output

Voltage 12VDC.

Current 1.2A supply current.

Other Short circuit and thermal overload protection.  
Filtered and regulated.

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

#### Indicators (LED)

Input Input voltage is present.

DC Output Powered.

#### Physical and Environmental

##### Enclosure Dimensions (H x W x D)

8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm).

Enclosure accommodates two (2) 12VDC/4AH batteries  
or one (1) 12VDC/7AH battery.

Product Weight 4.6 lbs. (2.1 kg).

Shipping Weight 5.15 lbs. (2.3 kg).

##### Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 7 BTU/Hr.